

UK - 2000

Industrial Flooring System

DESCRIPTION

UK-2000 is an industrial floor coating that's not only extremely quick, durable, and nearly odorless, but is also easy to use even in cold temps.

Ready for traffic in just one hour, UK-2000 is one industrial coating that won't slow you down.

RECOMMENDED USES

- ✓ Industrial facilities
- ✓ Freezers & coolers
- ✓ Correctional facilities
- ✓ Loading docks
- ✓ Pulp & paper mills



UK-2000

Industrial Flooring System

1265 N Hendrickson Dr Kalama WA 98625

360-673-6404

PERFORMANCE DATA

Compressive Strength

5,500, psi (ASTM C39)

Flexural Strength

2,500, psi

Tensile Strength

1,300, psi

Solids Content

99.8% based on EPA 160.3

Hardness

85, durometer "D"

Potlife

12 minutes

Coverage

Pre-packaged 4.25 gallon kit (65 lb) (w/filler) covers fifty (50) square feet @ 125 mils (1/8" thickness).

Consult with Absolute Protective Coatings for top coat recommendation (optional).

Colors

All Primary Colors

Packaging

2.125 gallon kit
4.25 gallon kit

Shipping Weight

65 lbs. per kit (4.25 gallon kit)



PRODUCT OVERVIEW

UK-2000 is a urethane hybrid overlay with fast cure rates and is traffic ready in 1 hour, even in cold temperatures.

UK-2000 is a unique blend of urethane-hybrid components and special fillers. This unique chemistry provides for super quick cure, no odor and a material that's VOC compliant. The result is a durable long-lasting surface in the tough industrial & commercial flooring environments.

BONDS WITHOUT PRIMER - No priming required in most applications.

FAST REPAIR & CURE - Initial set in 20 minutes, traffic ready in 60 minutes.

TYPICAL USAGE AND APPLICATIONS

SL GRADE (self-leveling slurry) UK-2000 is easily applied using a gage rake or notched trowel.

TROWEL GRADE (overlays and patching) UK-2000SL Grade is enhanced with aggregate filler to produce a high-build trowel-able mortar.

EMERY PLATE (high wear applications) UK-2000 is supplemented with extremely hard emery aggregate to create a heavy duty overlay/patching mortar.

For a demonstration of UK-2000 in your area, please call us at 360-673-6404 or send a note to absoluteconcretecolors@gmail.com.

RECOMMENDED READING

MSDS [Material Safety]
Product Data Sheet

Available online at
www.absoluteconcretecolors.net

Recommendations for product use based on tests believed to be reliable. Field conditions vary widely. For this reason, the user must determine product suitability for the particular use and specific applications. Absolute Protective Coatings, assumes no liability for injury, loss or damage resulting from use of this product. This product is not intended for retail distribution and should only be used by construction professionals experienced in the application and handling of potentially hazardous chemical compounds.